

Thermocouples, PT100, Ω , mV, V, mA, Frequency, Speed, AC V+A Digital Panel Meters

DS8B-IRRB



Universal Input Process Indicator

Features:	Input:	Ranges:
<ul style="list-style-type: none"> Fully programmable Full 4 digit dual display Accuracy $\pm 0.3\%$ FS 90~260V AC 50/60Hz ** Isolated - input / output / supply Two alarm relay outputs 4-20mA retransmission 24VDC/30mA transmitter supply Size: 48H x 96W x 100D 	mA	4 ~ 20 mA
	mV	0 ~ 75 mV
	V	0 ~ 10V DC
	T/C	K, J, E, T, R, S, B
	RTD	PT100
	Ω	0 ~ 400 Ω
	** Also available with 24VDC PS	

AC Voltage, Current & Power Indicator

Features:	Input:	Ranges:
<ul style="list-style-type: none"> Display V, A and one power CT and VT ratio scalable Full 4 digit triple display 90~260V AC 50/60Hz supply Isolated - input / output / supply Two alarm relay outputs 4-20mA retransmission Size: 48H x 96W x 78D 	A	0 ~ 5 A AC ($\pm 0.3\%$ FS)
	V	0 ~ 600 V AC ($\pm 0.5\%$ FS)
	Other functions:	
	KW	Instantaneous
	KWh	Totalizer
	PF	Instantaneous
	KVA	Instantaneous
KVAr	Instantaneous	
Hz	Instantaneous	



D800-IRR

FV8-FRL2I



Frequency, Tacho, Speed Indicator

Features:	Inputs and Ranges:
<ul style="list-style-type: none"> Fully programmable Full 6 digit dual display 85~265V AC 50/60Hz Isolated - input / output / supply Two alarm relay outputs 4-20mA retransmission 24VDC/80mA sensor supply Size: 48H x 96W x 90D 	Pulse, Square Wave (L=0~1V / H=3~30V)
	Frequency 0.001~10KHz
	Dry Contact (leading edge)
	NPN / PNP selectable
	Factor Setting 0.0001 to 99.9999

Various Transmitters Available:

- Pressure
- Level (submersible pressure)
- Humidity
- Temperature
- Light
- Air Velocity
- And more



Contact us for more details on your application