



RUNRITE
ELECTRONICS

(PTY) LTD

REG NO: 2016/537256/07

ESTABLISHED 1996

VAT NO: 4340162256

Unit 2, 17 Caversham Road, Pinetown, Kwa-Zulu Natal, Republic of South Africa

FS-600 Nuclear Radiation Detector



Material: ABS

Color: Black & White

Detector: glass type G-M counter tube

Measuring range: 0.1 μ Sv/h-10mSv/h

Dosage: 0.00 μ Sv-10Sv

Sensitivity: > 1cps/uSv/h (relative to 60Co)

The maximum dose equivalent rate: 99.99 μ sv/h

Voice source: real particle sound / alarm sound /mute

Alarm threshold: 0.5 (Adjustable)

The use of ambient temperature: -25 ~+45°C

Relative humidity: less than 95%

Energy response: 48keV-1.5MeV

Relative intrinsic error: < 10% (at 1mSv/h)

Power supply: 3 x AAA battery (Not included) or USB cable (included)

Power consumption: < 150mW

Temperature characteristics: -10°C~+ 50°C

Item size: 116*60*25(mm)

Item weight: 145g / 5.1ounce

Package size: 160*60 *25mm

Package weight: 160g

P.O. Box 208, Sarnia, 3615 • Tel: +27 (0) 87 806 5570 • info@runrite.co.za • Fax: +27 (0) 86 010 7601 • www.runrite.co.za

Alcolizer
technology

Delta
OHM

Honeywell



ZENITH
INSTRUMENTS